

1 Identification

- **Product identifier**
 - *Product number* TN931
 - *Trade name:* **KLIMA WB THIXO WOOD-TONE SATIN**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
1.3.2 Importer

 - Name I.C. & S. DISTRIBUTING CO.
Address P.O. BOX 10845
LANCASTER. PA
USA
E-Mail: nelson@ics-company.com
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:* 001 813-248-0585

2 Hazard(s) identification

- **Classification of the substance or mixture**



Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
- *Hazard pictograms*



- *Signal word* Warning
- *Hazard-determining components of labeling:*
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)
1,2-benzisothiazol-3(2H)-one
a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
- *Hazard statements*
H317 May cause an allergic skin reaction.
- *Precautionary statements*
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P280 Wear protective gloves.
P321 Specific treatment (see on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)

Product number TN931
Trade name: KLIMA WB THIXO WOOD-TONE SATIN

(Contd. of page 1)

P363 Wash contaminated clothing before reuse.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

· **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 1
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



HEALTH 0 Health = 0
FIRE 1 Fire = 1
REACTIVITY 0 Reactivity = 0

3 Composition/information on ingredients

Chemical characterization: Mixtures

· **Description:** Mixture: consisting of the following components.

Dangerous components:

34590-94-8	(2-methoxymethylethoxy)propanol Flam. Liq. 4, H227	1-<5%
112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye Irrit. 2A, H319	1-2.49%
	Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) ⚠ Aquatic Chronic 2, H411 ⚠ Skin Sens. 1, H317	0.5-1%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330 ⚠ Skin Corr. 1B, H314 ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1) ⚠ Skin Sens. 1, H317	≤0.0015%

4 First-aid measures

Description of first aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

(Contd. on page 3)

Product number TN931**Trade name: KLIMA WB THIXO WOOD-TONE SATIN**

(Contd. of page 2)

· Information for doctor:

- **Most important symptoms and effects, both acute and delayed**
For symptoms and effects caused by substances, refer to Section 11.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.**· Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals**· PAC-1:**

34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m

· PAC-2:

34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m

· PAC-3:

34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m

US

(Contd. on page 4)

Product number TN931**Trade name: KLIMA WB THIXO WOOD-TONE SATIN**

(Contd. of page 3)

7 Handling and storage

- **Handling:**

- *Precautions for safe handling* No special precautions are necessary if used correctly.
- *Information about protection against explosions and fires:* No special measures required.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- *Requirements to be met by storerooms and receptacles:*

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- *Information about storage in one common storage facility:* Not required.

- *Further information about storage conditions:* None.

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- *Components with limit values that require monitoring at the workplace:*

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

34590-94-8 (2-methoxymethylethoxy)propanol

PEL Long-term value: 600 mg/m³, 100 ppm
Skin

REL Short-term value: 900 mg/m³, 150 ppm
Long-term value: 600 mg/m³, 100 ppm
Skin

TLV Short-term value: 909 mg/m³, 150 ppm
Long-term value: 606 mg/m³, 100 ppm
Skin

112-34-5 2-(2-butoxyethoxy)ethanol

TLV Long-term value: 67.5* mg/m³, 10* ppm
*Inhalable fraction and vapor

· *Additional information:* The lists that were valid during the creation were used as basis.

- **Exposure controls**

- *Personal protective equipment:*

- *General protective and hygienic measures:*

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- *Breathing equipment:* Not required.

- *Protection of hands:*



Protective gloves

(Contd. on page 5)

US

Product number TN931**Trade name: KLIMA WB THIXO WOOD-TONE SATIN**

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Fluid

- **Color:**

According to product specification

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Not determined.

- **Change in condition**

- **Melting point/Melting range:**

Undetermined.

- **Boiling point/Boiling range:**

100 °C (212 °F)

- **Flash point:**

100 °C (212 °F)

- **Flammability (solid, gaseous):**

Not applicable.

- **Ignition temperature:**

225 °C (437 °F)

- **Decomposition temperature:**

Not determined.

- **Auto igniting:**

Product is not selfigniting.

- **Danger of explosion:**

Product does not present an explosion hazard.

- **Explosion limits:**

- **Lower:**

0.9 Vol %

- **Upper:**

14 Vol %

- **Vapor pressure at 20 °C (68 °F):**

0.4 hPa (0.3 mm Hg)

- **Density at 20 °C (68 °F):**

1.035 g/cm (8.637 lbs/gal)

- **Relative density**

Not determined.

- **Vapor density**

Not determined.

- **Evaporation rate**

Not determined.

- **Solubility in / Miscibility with**

- **Water:**

Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):**

Not determined.

- **Viscosity:**

- **Dynamic:**

Not determined.

- **Kinematic at 20 °C (68 °F):**

60 s (ISO 6 mm)

(Contd. on page 6)

Product number TN931
Trade name: KLIMA WB THIXO WOOD-TONE SATIN

(Contd. of page 5)

· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	55.7 %	
· VOC content:	3.68 % 38.1 g/l / 0.32 lb/gl	
· Solids content:	40.5 %	
· Other information (HAPS)		
112-34-5	2-(2-butoxyethoxy)ethanol	1-2.49%
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%
122-99-6	2-Phenoxyethanol	<0.01%
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
 - **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
34590-94-8 (2-methoxymethylethoxy)propanol		
Oral	LD50	5,135 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	19,020 mg/kg (rab)
112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	LD50	6,600 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	2,764 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)		
Oral	LD50	5,001 mg/kg (rat/szczur/mouse/souris/Maus/ratón) (OECD - 401)
Dermal	LD50	2,001 mg/kg (rat/szczur/mouse/souris/Maus/ratón) (OECD - 402)

- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
Irritant
Contains Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-

(Contd. on page 7)

Product number TN931**Trade name: KLIMA WB THIXO WOOD-TONE SATIN**

(Contd. of page 6)

hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene), 1,2-benzisothiazol-3(2H)-one, a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1). May produce an allergic reaction.
 Safety data sheet available on request.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

34590-94-8 (2-methoxymethylethoxy)propanol

EC50	970 mg/l (algae) (72 h)
	1,919 mg/l (daphnia) (48 h)
LC50 (96h)	1,001 mg/l (Fish)

112-34-5 2-(2-butoxyethoxy)ethanol

EC50	101 mg/l (algae) (48 h)
	101 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)

Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

EC50	101 mg/l (algae) (72h)
	4 mg/l (daphnia) (OECD linee guida 202 parte 1)
LC50 (96h)	2.8 mg/l (Leuciscus idus melanotus) (OECD linee guida 203)

55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

EC50	0.027 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.

- **Substances Easily biodegradable**

34590-94-8	(2-methoxymethylethoxy)propanol	.
112-34-5	2-(2-butoxyethoxy)ethanol	.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

(Contd. on page 8)

US

Product number TN931**Trade name: KLIMA WB THIXO WOOD-TONE SATIN**

(Contd. of page 7)

- **Additional ecological information:**

- **General notes:**

- Water hazard class 1 (Self-assessment): slightly hazardous for water

- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Hand over to hazardous waste disposers.

- Dispose of contents and container in accordance with local state and federal regulations.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- DOT, ADN, IMDG, IATA

Not applicable

- **UN proper shipping name**

- DOT, ADN, IMDG, IATA

Not applicable

- **Transport hazard class(es)**

- DOT, ADR, ADN, IMDG, IATA

- Class

Not applicable

- **Packing group**

- DOT, IMDG, IATA

Not applicable

- **Environmental hazards:**

- Marine pollutant:

No

- **Special precautions for user**

Not applicable.

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

- **UN "Model Regulation":**

Not applicable

15 Regulatory information

- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings) :**

112-34-5	2-(2-butoxyethoxy)ethanol	1-2.49%
1336-21-6	ammonia	<0.1%
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%

(Contd. on page 9)

Product number TN931**Trade name: KLIMA WB THIXO WOOD-TONE SATIN**

(Contd. of page 8)

111-76-2	2-butoxyethanol	<0.01%
122-99-6	2-Phenoxyethanol	<0.01%

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- TSCA new (21st Century Act) (Substances not listed)
- Proposition 65

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

111-76-2	2-butoxyethanol	NL	<0.01%
----------	-----------------	----	--------

- **TLV (Threshold Limit Value established by ACGIH)**

111-76-2	2-butoxyethanol	A3
----------	-----------------	----

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
- **Date of preparation / last revision** 02/08/2018 / 16

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Liq. 4: Flammable liquids . Category 4
 Acute Tox. 3: Acute toxicity . Category 3

(Contd. on page 10)

Safety Data Sheet
29 CFR Parts 1910 1915 1926

Printing date 02/08/2018

Version number 17

Reviewed on 02/08/2018

Product number TN931**Trade name: KLIMA WB THIXO WOOD-TONE SATIN**

(Contd. of page 9)

*Acute Tox. 2: Acute toxicity . Category 2**Skin Corr. 1B: Skin corrosion/irritation . Category 1B**Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A**Skin Sens. 1: Skin sensitisation . Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard . Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2***• Sources****REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments***Agency ECHA web site**INRS Fiche Toxicologique**IARC International agency for research on cancer***• * Data compared to the previous version altered.**

US