

## 1 Identification

### Product identifier

- *Product number* TS18
- *Trade name:* **ACRY-URETH ULTRA-MATT SELFSEAL**
- *Relevant identified uses of the substance or mixture and uses advised against*  
Paint and relative material only for wood
- *Application of the substance / the mixture* For professional use

### Details of the supplier of the safety data sheet

- *Manufacturer/Supplier:*  
IVM Chemicals Srl  
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

- *Information department:*  
Environmental Health and safety office  
hseoffice@ivmchemicals.com

### Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

### Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

### Label elements

#### GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

#### Hazard pictograms



GHS02



GHS07



GHS08

#### Signal word Danger

#### Hazard-determining components of labeling:

toluene

ethylbenzene

**Product number TS18**

**Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**

(Contd. of page 1)

methyl methacrylate

**Hazard statements**

- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P260 Do not breathe vapours.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:**

**NFPA ratings (scale 0 - 4)**



**HMIS-ratings (scale 0 - 4)**



**3 Composition/information on ingredients**

**Chemical characterization: Mixtures**

**Description:** Mixture: consisting of the following components.

**Dangerous components:**

108-88-3	toluene	30-49.9%
	<ul style="list-style-type: none"> <li>Flam. Liq. 2, H225</li> <li>Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304</li> <li>Skin Irrit. 2, H315; STOT SE 3, H336</li> </ul>	
141-78-6	ethyl acetate	25-29.9%
	<ul style="list-style-type: none"> <li>Flam. Liq. 2, H225</li> <li>Eye Irrit. 2, H319; STOT SE 3, H336</li> </ul>	
110-19-0	isobutyl acetate	12.5-15%
	<ul style="list-style-type: none"> <li>Flam. Liq. 2, H225</li> </ul>	
1330-20-7	xylene	5-9.99%
	<ul style="list-style-type: none"> <li>Flam. Liq. 3, H226</li> <li>Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315</li> </ul>	

(Contd. on page 3)

Printing date 09/18/2014

Reviewed on 09/18/2014

**Product number TS18**

**Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**

		(Contd. of page 2)
123-86-4	n-butyl acetate <div> <div>Flam. Liq. 3, H226</div> <div>STOT SE 3, H336</div> </div>	1-<10%
100-41-4	ethylbenzene <div> <div>Flam. Liq. 2, H225</div> <div>Carc. 2, H351</div> <div>Acute Tox. 4, H332</div> </div>	1-2.49%
80-62-6	methyl methacrylate <div> <div>Flam. Liq. 2, H225</div> <div>Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335</div> </div>	0.1-<0.5%

#### 4 First-aid measures

##### · Description of first aid measures

###### · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

###### · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

###### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

###### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.

###### · After swallowing: Do not induce vomiting; immediately call for medical help.

##### · Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

##### · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

##### · Extinguishing media

· Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

##### · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

##### · Advice for firefighters

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

#### 6 Accidental release measures

##### · Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

**Product number TS18**

**Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**

(Contd. of page 3)

- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to Section 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Protect against electrostatic charges.  
Use explosion-proof apparatus / fittings and spark-proof tools.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
  - **Storage:**
    - **Requirements to be met by storerooms and receptacles:**  
Store in a cool, well-ventilated area, away from heat and sources of ignition  
Provide solvent resistant, sealed floor.  
Observe the label precautions, the expiration date for the use, if indicated, is from delivery date of goods.  
In cases where there is no reported expiration date, it means that the product must be used within 8 months.
    - **Information about storage in one common storage facility:** Not required.
    - **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

### 108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI

### 141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m <sup>3</sup> , 400 ppm
-----	---

(Contd. on page 5)

Printing date 09/18/2014

Reviewed on 09/18/2014

**Product number TS18**

**Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**

(Contd. of page 4)

REL Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm

TLV Long-term value: 1440 mg/m<sup>3</sup>, 400 ppm

**110-19-0 isobutyl acetate**

PEL Long-term value: 700 mg/m<sup>3</sup>, 150 ppm

REL Long-term value: 700 mg/m<sup>3</sup>, 150 ppm

TLV Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

**1330-20-7 xylene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 434 mg/m<sup>3</sup>, 100 ppm  
BEI

**123-86-4 n-butyl acetate**

PEL Long-term value: 710 mg/m<sup>3</sup>, 150 ppm

REL Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 710 mg/m<sup>3</sup>, 150 ppm

TLV Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

**100-41-4 ethylbenzene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL Short-term value: 545 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm  
BEI

**· Ingredients with biological limit values:**

**108-88-3 toluene**

BEI 0.02 mg/L  
Medium: blood  
Time: prior to last shift of workweek  
Parameter: Toluene

0.03 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Toluene

0.3 mg/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: o-Cresol with hydrolysis (background)

**1330-20-7 xylene**

BEI 1.5 g/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Methylhippuric acids

(Contd. on page 6)

Printing date 09/18/2014

Reviewed on 09/18/2014

**Product number TS18**

**Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**

(Contd. of page 5)

**100-41-4 ethylbenzene**

BEI	0.7 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	
	Medium: end-exhaled air
	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

(Contd. on page 7)

USA



Printing date 09/18/2014

Reviewed on 09/18/2014

**Product number TS18**  
**Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**

(Contd. of page 6)

· <b>Color:</b>		According to product specification
· <b>Odor:</b>		Characteristic
· <b>Odour threshold:</b>		Not determined.
· <b>pH-value:</b>		Not determined.
· <b>Change in condition</b>		
· <b>Melting point/Melting range:</b>		Undetermined.
· <b>Boiling point/Boiling range:</b>		77 °C (171 °F)
· <b>Flash point:</b>		-4 °C (25 °F)
· <b>Flammability (solid, gaseous):</b>		Not applicable.
· <b>Ignition temperature:</b>		370 °C (698 °F)
· <b>Decomposition temperature:</b>		Not determined.
· <b>Auto igniting:</b>		Product is not selfigniting.
· <b>Danger of explosion:</b>		Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>		
· <b>Lower:</b>		1.0 Vol %
· <b>Upper:</b>		11.5 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>		97 hPa (73 mm Hg)
· <b>Density at 20 °C (68 °F):</b>		0.911 g/cm³ (7.602 lbs/gal)
· <b>Relative density</b>		Not determined.
· <b>Vapour density</b>		Not determined.
· <b>Evaporation rate</b>		Not determined.
· <b>Solubility in / Miscibility with</b>		
· <b>Water:</b>		Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>		Not determined.
· <b>Viscosity:</b>		
· <b>Dynamic:</b>		Not determined.
· <b>Kinematic at 20 °C (68 °F):</b>		55 s (ISO 6 mm)
· <b>Solvent content:</b>		
· <b>VOC content:</b>		84.3 % 768.4 g/l / 6.41 lb/gl
· <b>Solids content:</b>		15.7 %
· <b>Other information (HAPS)</b>		
108-88-3	toluene	30-49.9%
1330-20-7	xylene	5-9,99%
100-41-4	ethylbenzene	1-2,49%
80-62-6	methyl methacrylate	0.1-<0.5%

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.

(Contd. on page 8)

**Product number TS18**

**Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**

(Contd. of page 7)

- **Possibility of hazardous reactions**  
Reacts with strong acids and oxidizing agents.  
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
in case of possible formation of combustion:  
Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure.
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

### 108-88-3 toluene

Oral	LD50	5000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	12124 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	5320 mg/l (mouse) (4 h)

### 141-78-6 ethyl acetate

Oral	LD50	4934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Dermal	LD50	>20000 mg/kg (Con)
Inhalative	LC0/6 h	>22.5 ppm (mouse)
	LC50/4 h	1600 mg/l (rat/szczur/mouse/souris/Maus/ratón)

### 110-19-0 isobutyl acetate

Oral	LD50	13400 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	17401 mg/kg (Con)
Inhalative	LC50/4 h	31 mg/l (rat/szczur/mouse/souris/Maus/ratón)

### 1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	2000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)

### 123-86-4 n-butyl acetate

Oral	LD50	10760 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	14000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	>21.0 mg/l (rat/szczur/mouse/souris/Maus/ratón)

### 100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	17800 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)

### 80-62-6 methyl methacrylate

Oral	LD50	7872 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
------	------	---

- **Primary irritant effect:**
  - **on the skin:**  
Irritant to skin and mucous membranes.  
Causes skin irritation.
  - **on the eye:**  
Irritating effect.

(Contd. on page 9)



Printing date 09/18/2014

Reviewed on 09/18/2014

**Product number TS18**

**Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**

(Contd. of page 8)

- Causes serious eye irritation.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
  - Causes skin irritation.
  - Causes serious eye irritation.
  - Suspected of damaging the unborn child.
  - May cause drowsiness or dizziness.
  - May cause damage to organs through prolonged or repeated exposure.
  - Contains methyl methacrylate. May produce an allergic reaction.
  - Irritant
  - May cause drowsiness or dizziness.

· **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer)</b>		
108-88-3	toluene	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
9003-07-0	polypropylene	3
7631-86-9	silicon dioxide, chemically prepared	3
80-62-6	methyl methacrylate	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1

· <b>NTP (National Toxicology Program)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	K

· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

**12 Ecological information**

· **Toxicity**

· <b>Aquatic toxicity:</b>	
<b>108-88-3 toluene</b>	
EC50	134 mg/l (algae) 3.78 mg/l (invertebrates)
<b>141-78-6 ethyl acetate</b>	
EC50	164 mg/l (daphnia)
LC50 (96h)	(daphnia)
<b>110-19-0 isobutyl acetate</b>	
EC50	25 mg/l (daphnia)
<b>1330-20-7 xylene</b>	
EC50	1 mg/l (daphnia)
<b>123-86-4 n-butyl acetate</b>	
EC50	648 mg/l (algae) 72h 44 mg/l (daphnia) 48h
LC50 (96h)	18 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.

(Contd. on page 10)

USA

Printing date 09/18/2014

Reviewed on 09/18/2014

**Product number TS18**

**Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**



(Contd. of page 9)

- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
  - **General notes:**
    - Water hazard class 2 (Self-assessment): hazardous for water
    - Do not allow product to reach ground water, water course or sewage system.
    - Danger to drinking water if even small quantities leak into the ground.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
  - **Recommendation:**
    - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
    - Hand over to hazardous waste disposers.
    - Dispose of contents and container in accordance with local state and federal regulations.
- **Uncleaned packagings:**
  - **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |   |                     |
|---|---------------------|
| · <b>UN-Number</b>  |                     |
| · <b>DOT</b>  | NA1263              |
| · <b>IMDG, IATA</b>   | UN1263              |
| · <b>UN proper shipping name</b>  |                     |
| · <b>DOT</b>  | Paint               |
| · <b>IMDG, IATA</b>   | PAINT               |
| · <b>Transport hazard class(es)</b>   |                     |
| · <b>DOT</b>  |                     |
|  |                     |
| · <b>Class</b>  | 3 Flammable liquids |
| · <b>Label</b>  | 3                   |
| · <b>Class</b>  | 3 Flammable liquids |
| · <b>Label</b>  | 3                   |
| · <b>IMDG, IATA</b>   |                     |
|  |                     |
| · <b>Class</b>  | 3 Flammable liquids |
| · <b>Label</b>  | 3                   |
| · <b>Packing group</b>  |                     |
| · <b>DOT, IMDG, IATA</b>  | III                 |
| · <b>Environmental hazards:</b>   |                     |
| · <b>Marine pollutant:</b>  | No                  |

(Contd. on page 11)

Printing date 09/18/2014

Reviewed on 09/18/2014

**Product number TS18**

**Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**

(Contd. of page 10)

· **Special precautions for user**

· **Danger code (Kemler):**

· **EMS Number:**

Warning: Flammable liquids

33

F-E, S-E

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **IMDG**

· **Limited quantities (LQ)**

· **Excepted quantities (EQ)**

5L

Code: E1

Maximum net quantity per inner packaging:  
30 ml

Maximum net quantity per outer  
packaging: 1000 ml

· **UN "Model Regulation":**

UN1263, Paint, special provision 640H, 3, III

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Stannane, dioctyl-, bis(coco acyloxy) derivs

· **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

108-88-3 toluene

1330-20-7 xylene

100-41-4 ethylbenzene

80-62-6 methyl methacrylate

78-93-3 butanone

· **TSCA (Toxic Substances Control Act):**

toluene

ethyl acetate

isobutyl acetate

xylene

BUTIRRATO ACETATO DI CELLULOSA

Contenuto solido

n-butyl acetate

ethylbenzene

polypropylene

Polymer

polyethylene

Zinc stearate

silicon dioxide, chemically prepared

PROCOL 107 H

(Contd. on page 12)

Printing date 09/18/2014

Reviewed on 09/18/2014

**Product number TS18**  
**Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**

(Contd. of page 11)

2,4-dihydroxybenzophenone

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
14808-60-7	Quartz (SiO <sub>2</sub> )

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
64-17-5	ethanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
80-62-6	methyl methacrylate	E, NL

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
80-62-6	methyl methacrylate	A4
64-17-5	ethanol	A3
14808-60-7	Quartz (SiO <sub>2</sub> )	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO <sub>2</sub> )
------------	----------------------------

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
- **Date of preparation / last revision** 09/18/2014 / 69

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 13)

# Safety Data Sheet

## 29 CFR Parts 1910 1915 1926

Printing date 09/18/2014

Reviewed on 09/18/2014

**Product number TS18****Trade name: ACRY-URETH ULTRA-MATT SELFSEAL**

(Contd. of page 12)

VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 Flam. Liq. 2: Flammable liquids, Hazard Category 2  
 Flam. Liq. 3: Flammable liquids, Hazard Category 3  
 Acute Tox. 4: Acute toxicity, Hazard Category 4  
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A  
 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
 Carc. 2: Carcinogenicity, Hazard Category 2  
 Repr. 2: Reproductive toxicity, Hazard Category 2  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
 Asp. Tox. 1: Aspiration hazard, Hazard Category 1

• **Sources**

Directive 1999/45/EC and following amendments  
 Directive 67/548/EEC and following amendments and adjustments  
 Agency ECHA web site  
 INRS Fiche Toxicologique  
 IARC International agency for research on cancer

• \* **Data compared to the previous version altered.**

USA